

4.2-TON CLASS / CUMMINS DIESEL / HIGH-FLOW HYDRAULICS

TLS75

COMPACT TRACK LOADER

Built for demanding loading, grading, and attachment work. The TLS75 combines a 4,200 kg operating weight, 1,050 kg rated load, high-flow hydraulics, and a wide enclosed cab.

HIGH FLOW. FULL CONTROL. JOBSITE READY.

73.8 HP	9,260 LB	2,315 LB	17.7 FT3
CUMMINS DIESEL	OPERATING WEIGHT	RATED LOAD	BUCKET CAPACITY

TLS75 / TECHNICAL SPECIFICATIONS

ENGINE AND PERFORMANCE

Engine	**Cummins QSF2.8 EPA**
Rated power	**55 kW / 73.8 hp @ 2,500 rpm**
Operating weight	**4,200 kg / 9,260 lb**
Rated load	**1,050 kg / 2,315 lb**
Bucket capacity	**0.50 m3 / 17.7 ft3**
Track model	**320 x 86**
Max. speed	**12 / 18 km/h / 7.5 / 11.2 mph**
Max. traction	**>= 28.2 kN / 6,340 lbf**
Max. breakout	**>= 20 kN / 4,496 lbf**
Boom lift time	**7 seconds**

DIMENSIONS AND WORKING RANGE

Operating height	**3,480 mm / 11 ft 5.0 in**
Hinge pin height	**2,900 mm / 9 ft 6.2 in**
Cab / level bucket height	**2,150 / 2,730 mm**
Length with bucket	**3,500 mm / 11 ft 5.8 in**
Dumping height	**2,230 mm / 7 ft 3.8 in**
Dump angle / reach	**40 deg / 715 mm / 28.1 in**
Rollback ground / full	**30 deg / 104 deg**
Wheelbase	**1,500 mm / 4 ft 11.1 in**
Ground clearance	**200 mm / 7.9 in**
Turning radius front / rear	**1,298 / 1,714 mm**
Rear axle to bumper	**890 mm / 2 ft 11.0 in**
Tread / overall width	**1,462 / 1,782 mm**
Bucket width	**1,830 mm / 6 ft 0.0 in**

STANDARD INCLUDED HIGHLIGHTS

CUMMINS EPA
QSF2.8 / 55 kW

HIGH-FLOW HYDRAULICS
140 L/min

DUAL OPERATING MODES
Single / dual lever

WIDE CAB
Air-suspension seat

CLIMATE CONTROL
Cold and warm A/C

STANDARD CONFIGURATION

- Cummins QSF2.8 55 kW EPA engine
- Electronic controls
- Cold and warm air conditioning
- Wide cab package
- Air-suspension seat
- Rear-view camera
- 140 L/min high-flow hydraulic system
- Single / dual lever operating modes
- Hydraulic quick attach
- Reinforced top-mounted cooling system
- 400 mm tracks with undercarriage package
- Front windshield protective guard
- RAL 9005 matte black finish